



HT005E

WIRELESS SCREEN TRANSMISSION

The HT005E wireless screen transmission dongle connects to the USB port of a device and transmits the on-screen content to the Digital Whiteboard for everyone to see. Connect it to your device and with a single button press, the content will be instantly displayed on the whiteboard through fast and stable streaming (Windows / Mac supported).

Highlights



Go Click

Connect it to your laptop and with a single button press, the content will be instantly displayed on the IDB through fast and stable streaming (Windows and Mac supported simultaneously).



Touch Back

Support touch back, after casting the files (presentations/documents/sheets) of your laptop to your IDB, you can edit the related files on IDB, such as execute page turning, add comments, edit files



Fast and Stable

Quick to configure, fast response, almost no delay in screen cast, own efficient meetings.



Wireless Connection

No need HDMI / TYPE LAN and No need to download any application when using wireless casting dongle.

Specifications

HT005E	
Color	White
Logo	Hisense
Connect Number	1 received device (same time)
Button	1
Port	USB-C
Working Voltage	5V
Video Resolution	FHD 60Hz
Transmission Distance	15m
Main IC	RV1108A
Plug and Play	Support
WiFi Module	IEEE 802.11b/g/n/ac
Indicator Light	Blinking when connecting White color when using
Certification	TBC
Hot Plug	Support
Working Temperature	-10°C~+45°C
Working Humidity	≤95%
Adaptive Model	65WR6BE/75WR6BE/86WR6BE/65WR6CE/75WR6CE/86WR6CE/65MR 6DE/75MR6DE/86MR6DE

^{*}Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.



